

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Tumbled Ledge

- Standard Colors:** Aspen, Chablis, Dakota Brown, Madison County, Monterey, Nottingham, Sunset Blend or Any Custom Color
- Grout Joint Width:** ½" Grout Joint or Drystack
- Grouting Options:** Deep Raked, Drystack, Full Brushed or Full Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Should be no higher than 4" to 6" on average.
- Horizontal Joints:** Should not exceed 6' to 8'.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Drystack:** A polymer modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 1" to 4" in height and 4" to 20" in length (nominal). Tumbled Ledge contains **15% panels** for a fast and easy installation.
- Thickness:** 1½" to 3"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (100 sq ft Flats & 100 lft Corners) or Dura-Paks (12.5 sq ft Flats & 12.5 lft Corners).
When purchasing Tumbled Ledge, coverage is based on installation with tightly-fitted joints.

Drystack



TUMBLED LEDGE

COLOR: NOTTINGHAM

Drystack



TUMBLED LEDGE

COLOR: DAKOTA BROWN